## PA Amplifier with USB/SD & FM & Blue Tooth EA-120 (120W)

## Features:

- ✓ Compact mini size public address amplifier
- $\checkmark$  Ideal for classroom sound system use
- ✓ Built-in 100V/70V transformer technology
- $\checkmark$  Tabletop amplifier with Mp3 player, FM radio & blue tooth
- $\checkmark$  Rate power output at 30W, 60W to 120W.
- $\checkmark$  Speaker output of 100V or 70V & 40hms-8 Ohms-16 Ohms
- $\checkmark$  Mp3 player with USB/SD input on front panel, IR remote control for Mp3 player, FM radio and blue tooth
- $\checkmark$  LED indicators for power, clip, protect and signal
- Mic1-3 and line 1-2 and telephone input. Mic1 of balanced XLR input with phantom power on rear panel. Mic2-3 microphone or line switchable unbalanced 6.3mm phone jack input. Line 1-2 input of RCA input and one RCA line output. Telephone input with VOX priority and MOH (Music on Hold).
- $\checkmark$  Volume control for Mic1-3, line1-2, Mp3/FM, bass/treble and master
- $\checkmark$  ~ With short-circuit, clip, overload and high temp protection
- $\checkmark$   $\;$  AC220V or 115V & 24V DC both operation system

## Specification:

Model	EA-120
Description	PA Amplifier with USB/SD & FM & Blue Tooth
Rated Power Output	120W
Speaker Outputs	100V or 70V & 40hms-8 0hms-16 0hms
Connector	Mic1 input by balanced XLR with phantom power
	Input2-3 inputs Mic/Line switchable unbalanced 6.3mm phone jack
	Line1-2 inputs by RCA; Line output by RCA
Attenuation	Microphone1-3, line1-2 and Mp3/FM, bass/treble and master
Input	MIC1-3: 5-8mV, 600 $\Omega$ ; Line, 150-470mV, 10K $\Omega$ , unbalanced RCA
Line Out	0.775(0dBV)
Frequency Response	60Hz-15kHz(±3dB)
S/N Ratio	Line $\geq$ 85dB, Mic $\geq$ 72dB
THD	Less than 0.5%
Protection	short-circuit, clip, overload and high temp protection
Power Consumption	200W
Power Supply	AC220V or 115V & 24V DC /50-60Hz
Dimension	320(W)×210(D)×90(H)mm
Weight	4.9kg

## **Rear Panel:**



